LAUFEN INSTALLATION SYSTEM

CWB101 Concealed frame for washbasin 91010.1



Order no.	91010.1	Installation depth	min. 98 mm
matching for	All LAUFEN washbasins with wall-fixation	Weight	8,2 kg
	50 - 400 mm	Mounting acc. incl.	Fastening set to floor, fastening set for ceramic
Specifications	Self-supporting steel frame for covering with		protection tubes for M10 threaded rods and
	plasterboard, installation onto a solid wall, in		outlet pipe Ø 40-50 mm.
	drywall constructions.	Mounting acc. excl.	Fastening set for wall, order no. 89563.5
	Height-adjustable concealed trap DN 50 (d:50) /		Sound insulation set, order no. 89269.6
	DN 40 (d:40).	Accessories excl.	Cover for siphon, order no. 97511.2
Other specifications	Galvanized leg supports, rotatable,	Mounting information	Height from finished floor to top of washbasin
	height-adjustable 0-200 mm.		pre-set to 900 mm, adjustable between
	Capable to resist 150 kg		850-900 mm.
Water connection	The height distance is adjustable between	Colours	Surface powder coated blue
	200-690 mm.		
Outlet	Ø 40-50 mm		

TECHNICAL DRAWINGS / S 1 : 20



