

LAUFEN INSTALLATION SYSTEM

TW102

Concealed frame with cistern for wallhung WC

92610.2



TECHNICAL DATA

Order no.	92610.2	Installation depth	125 mm
Certified to	EN 14055	Weight	6,3 kg
matching for	All LAUFEN wallhung toilets	Mounting acc. incl.	Wall bracket, protection box for access opening, retaining bolts with protection plugs, angle valve R 1/2, WC connector 90° (Ø 90 mm), PE transition sleeve Ø 90 / 110 mm, WC connection set Ø 90 mm, L=180 mm, mounting material.
Specifications	U-shaped galvanised support frame, for installation in/onto solid walls. With front operated. Dual-Flush 6/3-l (4/3-l-flush), with water condensation insulation. Fill valve Noise Class I.	Mounting acc. excl.	Support set to floor, order no. 97511.1
Other specifications	Galvanized supporting "U-shaped" with fixing points adjustable to the wall. Capable to resist 400 kg	Accessories excl.	Actuator plates dual flush, order no. 90010.0, 90010.1, 90010.2 (glass), 90010.3 (stainless steel), 90010.4, 90010.5, 90010.6, Electronic actuator plate dual flush, order no. 90010.7 (glass)
Water inlet	rear R 1/2, brass, matching for standard pipe systems	Mounting information	Height from finished floor to top of WC pre-set to 400 mm.
Outlet	DN 90/110	Colours	Surface galvanized
Flow pressure range	0.5-10 bar		
Water temperature	max. 25°C		
Tank	Installation depth: 120 mm, material PP		

TECHNICAL DRAWINGS / S 1 : 20

